



ESI eSIP and eCloud

AC600M USB Wi-Fi Dongle Datasheet

The AC600M Wi-Fi Dongle is a low-power, small form factor device that can be deployed within offices for connecting IP phones to available wireless networks.

This dynamic plug-and-play style USB device is an ideal office networking solution for companies, particularly smaller organizations seeking affordable, convenient and reliable high-speed wireless connectivity.

Supported by a powerful transmission rate of 150 Mbps, the solution is able to quickly and reliably establish Wi-Fi connectivity so that users can optimally communicate.

Safe, reliable and easy deployment guarantees a flexible and optimal user experience.

Even more, the Wi-Fi USB Dongle is compliant with IEEE802.11n, IEEE802.11b/g, and 802.11ac standards, maximizing reliability and throughput.



Highlights

- Compatible with ESI ePhone3 (v2), ePhone4x (v2), ePhoneX, and ePhoneX-1 (Only supports 2.4GHz/150Mbps)
- Ease-of-use
- High Transmission Rate
- Plug and Play
- Lower Power Consumption

Product Specifications

- Network standard IEEE802.11b/g/n, 802.11ac
- Transmission rate: 150Mbps, 433MHz
- Frequency range: 2.4GHz, 5.8GHz
- Security: WFA, WPA, WPA2, WPS2.0, WAPI
- Interface: USB2.0
- Working Temperature: 32-113°F (0-45°C)
- Working humidity: 20-85%

Packaging Specifications

- Color: Black
- Device dimensions: 1.3x0.63x0.28in (33x16x7mm)
- Package dimensions: 4.3x3.7x0.6in (110x95x15mm)

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.